

IN THE CLAIMS

1. (Original) A method of determining service criteria for a printhead in a printer comprising:

receiving an indication that service is needed;

determining a calculated age of said printhead; and

selecting a service procedure based on the determined calculated age.

(11 Cont.)
2. (Original) The method of claim 1, wherein said selected service procedure has an impact on the long term life of said printhead that is proportional to the calculated age.

3. (Original) The method of claim 1, further comprising classifying said calculated age as one of a plurality of phases.

4. (Original) The method of claim 3, wherein said plurality of phases include at least a beginning of life phase and a maturity phase.

5. (Original) The method of claim 3, wherein said plurality of phases include at least a beginning of life phase, a middle of life phase and a maturity phase.

6. (Original) The method of claim 5, wherein said selected service procedure for said beginning of life phase has a low impact on the long term life of said printhead.

7. (Original) The method of claim 5, wherein said selected service procedure for said middle of life phase has a moderate impact on the long term life of said printhead.

8. (Original) The method of claim 5, wherein said selected service procedure for said maturity phase has a severe impact on the long term life of said printhead.

9. (Original) The method of claim 1, wherein determining said calculated age comprises utilizing at least one factor selected from the group consisting of: volume of ink expelled, type of previous service procedures, number of previous service procedures,

types of previous failures, number of previous failures, time and number of print jobs printed.

10. (Original) An apparatus for determining service criteria for a printhead in a printer comprising:

circuitry for receiving an indication that service is needed; and

C1 a processor for determining a calculated age of said printhead and selecting a service procedure based on the determined calculated age.

11. (Original) The apparatus of claim 10, wherein said selected service procedure has an impact on the long term life of said printhead that is proportional to said calculated age.

12. (Previously presented) The apparatus of claim 10, further comprising circuitry for classifying said calculated age as one of a plurality of phases.

13. (Previously presented) The apparatus of claim 12, wherein said plurality of phases include at least a beginning of life phase and a maturity phase.

14. (Previously presented) The apparatus of claim 12, wherein said plurality of phases include at least a beginning of life phase, a middle of life phase and a maturity phase.

15. (Previously presented) The apparatus of claim 14, wherein said selected service procedure for said beginning of life phase has a low impact on the long term life of said printhead.

16. (Previously presented) The apparatus of claim 14, wherein said selected service procedure for said middle of life phase has a moderate impact on the long term life of said printhead.

17. (Previously presented) The apparatus of claim 14, wherein said selected service procedure for said maturity phase has a severe impact on the long term life of said printhead.

18. (Previously presented) The apparatus of claim 10, wherein said processor for determining said calculated age comprises utilizing at least one factor selected from the group consisting of: volume of ink expelled, type of previous service procedures, number of previous service procedures, types of previous failures, number of previous failures, time and number of print jobs printed.

C1
End

19. (Previously presented) The apparatus of claim 10, wherein said service procedure has a prolonging impact on the useful life of said printhead.

20. (Previously presented) The method of claim 1, wherein said service procedure has a prolonging impact on the useful life of said printhead.

21. (New) The method of claim 1, wherein said selected procedure services nozzles of said printhead that are selected based on a failed health thereof, then checks the health of said selected nozzles and repeats said selected service procedure if said printhead is determined to be operating inadequately.
